

PERFECT FIT™

SIDE EMITTING LED RIBBON by Northwest LED



Professional quality, energy efficient ribbon light available in single and double row options to meet your lighting needs.

Our Side Emitting LED ribbon is dimmable, low voltage lighting that emits light from the edge of the strip, making it suitable for use in areas where a “wall wash” effect is desired, especially along curved surfaces where typical top mounted LED ribbon won’t do. Comes standard in 16.4 foot rolls.

Features

- Color Rendering Index (CRI) > 90
- 3M Adhesive backing adheres to most surfaces.
- White, 2-foot leads on both ends of roll for easier installation.
- UL certified-conforms to UL Std. 2108.
- Dimmable (when powered with approved dimmable driver).
- Easily cut to required length.
- Available in custom lengths or with custom lead lengths.

LED Color Temperature

2700 k	Incandescent White
3000 k	Halogen White
4000 k	Natural White



LinR12-MB-SE-IP20



LinR24-DB-SE-IP20

Style & Brightness	Part # 12=12V 24=24V	Color	Lumens/ Ft.	Watts/ Ft.	Watts/ Roll	LEDs per roll	Cut interval	Ribbon width	Typical Uses
Medium Bright Wet IP67 (standard)	LinR12-MB-SE	27k 30k 40k	130	1.5	24	600	1"	5 mm IP20 8 mm IP67	Wall wash on radius surfaces, such as bars.
Dual Bright output Dry IP20 (standard) Special order only	LinR24-DB-SE	27k 30k 40k	360	3.7	60	1200	2"	8 mm IP20	“Up and Down” lighting useful on curved surfaces or backlighting.

Northwest LED

Linear LED lighting

Example part numbers

LinR12-MB-27k-SE-IP67= Ribbon, 12VDC, Medium Bright output, 2700k, Side Emitting, Wet rated
 LinR24-DB-30k-SE = Ribbon, 24VDC, Dual Bright output, 3000k, Side Emitting