# PERFECT FIT

Job Name		
Notes		

VASHON Fixture Series by Northwest LED

## Professional quality, <u>custom</u> LED light fixtures without the custom price!



Vashon-RO I" wide x I 3/32" tall

IIIR (Surface Mount)

IIIR-PEN (Pendant)





#### **Features**



- ETL certified fixtures conform to UL Std 2108 and NEC requirements.
- Color Rendering Index (CRI) of 95 or above. Brings out true colors.
- Dimmable when powered with an approved dimmable driver. (sold separately)
- Custom fabricated in the USA in lengths from 6 to 118-inches.
- Surface and Pendant styles available.
- 2-year warranty when powered with a Northwest LED approved driver.

Brightness Options	Voltage DC	Watts/ Ft.	LEDs/ Ft.	Lumen/ Ft.
Extra Bright (XB)	12/24	4.4	36	400
COB (CB)	24	4.6	N/A	521
Ultra Bright (UB)	24	5.5	39	763
Dual Bright (DB)	24	5.9	72	700
Warm Dim (WD)	24	2.9	68	275

### **Mounting Options**

#### Surface mounted

Mounts using metal clips that attach to a solid surface and clip into a groove on the back of the fixture.

#### **Pendant**

Includes 2 stainless steel suspension wire sets that allows adjustable suspension heights from 3 to 78-inches.

#### Recessed

Includes spring clips to allow mounting securely in ceiling installations.



LED Color Options		
27-18 k	Warm Dim 2700k dims to 1800k	
2700 k	Incandescent White	
3000 k	Halogen White	
3500k	Architectural White	
4000 k	Natural White	
5000 k	Clinic White	



## **Ordering Information**

PERFECT FIT™ VASHON series surface mount fixtures comes standard in "Silver" finish with a single 2 foot long lead wire and mounting clips. Pendant fixtures come standard with 2 sets of suspension hardware and 8 foot lead wire. The Vashon-R comes standard with spring clips. Please specify the housing & mounting style, color temperature, brightness level and finished length for each fixture. Fixtures may optionally be ordered with extra long leads, or in custom configurations (square, rectangle etc.). Finish options other than silver generally require additional lead time. Please call for availability and pricing.

Examples: LinF24-106f-PEN-DB-30k-60 LinF24-029f-XB-40k-96-L10

Model	Lens	Brightness	Color Temp	Fixture Length In Inches	Options
LinF12/24-104 LinF12/24-111R LinF12/24-106 LinF12/24-109 LinF12/24-111S LinF12/24-029 LinF12/24-105	f = frosted	XB=Extra Bright CB=COB DB=Dual Bright UB=Ultra Bright WD= Warm Dim	27k=2700k 50k=5000k 30K=3000k 35k=3500k 40k=4000k 27k-18k	6 (minimum) to 192 (maximum)	L=lead length (2' std.)
Pendant versions of above models: PEN	f	Same as above	Same as above	6 to 78	L=lead length (8' std)