

PERFECT FIT™

WHIDBEY Fixture Series by Northwest LED

Job Name
Notes

Professional quality, custom LED light fixtures without the custom price!

Whidbey-R 017 (Recessed)
Flange width = 1 15/16"
Inset = 1 3/8" wide x 1 11/32" deep



Whidbey 1 3/8" W x 1 3/8" H
018 (Surface Mount)
018 PEN (Pendant)



Whidbey-2 1 15/16" W x 1 3/8" H
046 (Surface Mount)
046 PEN (Pendant)



Whidbey-3 2 15/16" W x 1 3/8" H
048 (Surface Mount)
048 PEN (Pendant)



LED Color Options	
27-18 k	Warm Dim 2700k dims to 1800k
2700 k	Incandescent White
3000 k	Halogen White
3500 k	Architectural White
4000 k	Natural White

Finish Options			
Silver (Std.)		Bronze	
White		Black	

Features

- ETL certified fixtures conform to UL Std 2108 and NEC requirements. 
- Color Rendering Index (CRI) of 95 or above. Brings out true colors.
- Dimmable when powered with an approved dimmable driver. (sold separately)
- Custom fabricated in the USA in lengths from 6 to 192-inches. (Longer fixtures and custom configurations available - contact us for details).
- Surface, Recessed and Pendant styles available.
- 2-year warranty when powered with a Northwest LED approved driver.

Brightness Options	Voltage DC	Watts/ Ft.	LEDs/ Ft.	Lumen/ Ft.
Extra Bright (XB)	12/24	4.4	36	400
Dual Bright (DB)	24	5.9	72	700
Dual Bright x 2 (2DB)	24	11.8	144	1400
Warm Dim (WD)	24	3.9	68	275
Warm Dim x 2 (2WD)	24	5.8	136	550
Ultra Bright (UB)	24	5.9	39	763
Ultra Bright x 2 (2UB)	24	11.8	78	1526

Mounting Options

Surface mounted
Metal clips that screw to a solid surface, then snap into a groove on the back of the fixture.



Pendant

Includes 2 aircraft cable sets that allow adjustable suspension heights from 3 to 78 inches.



Recessed

Includes spring clips to fit fixtures securely into ceiling installations.



Ordering Information

PERFECT FIT™ Whidbey Models come standard in "Silver" finish with a single 2 foot long lead wire and appropriate mounting clips. Pendant style fixtures come standard with 2 sets of suspension hardware and 8 foot lead wire. Please specify the housing & mounting style, color temperature, brightness level and finished length for each fixture. Fixtures may *optionally* be ordered with extra long leads, or in custom configurations (square, rectangle, longer than 192-inches etc.). Finish options other than silver generally require additional lead time. Please call for availability and pricing.

**Examples: LinF24-018PENf-DB-30k-98-L10
LinF24-046f-2WD-96**

Model	Lens	Brightness	Color Temp	Fixture Length (In Inches)	Options
LinF12/24-017 LinF12/24-018 LinF12/24-046 LinF12/24-048	f=frosted	XB=Extra Bright DB/2DB= Dual Bright/x2 UB/2UB = Ultra Bright/x2 WD/2WD=Warm Dim/x2	27k=2700k 40k=4000k 30k=3000k 35k=3500k 2700k-1800k	6 (minimum) to 192 (maximum)	L=longer lead (2' standard) Wet = Wet Location
LinF12/24-018 PEN	f	XB, DB, 2DB, UB, 2UB, UB, 2UB, / WD, 2WD	27k, 30k, 35k, 40k / 27-18k	6 to 192	L (8' standard)
LinF12/24-046 PEN	f	XB, DB, 2DB, UB, 2UB, UB, 2UB, / WD, 2WD	27k, 30k, 35k, 40k / 27-18k	6 to 192	L
LinF12/24-048 PEN	f	XB, DB, 2DB, UB, 2UB, UB, 2UB, / WD, 2WD	27k, 30k, 35k, 40k / 27-18k	6 to 192	L

Northwest LED

Linear LED lighting

1404 Riverside Dr., Ste. F, Mount Vernon, WA 98273 • 360.422.5387 • www.NorthwestLED.com • info@northwestLED.com