

PERFECT FIT

Electronic LED Drivers to power Perfect Fit Fixtures & Ribbon

Job Name

Notes

SC KVF Series - Compact, hardwired and compatible with most ELV /Triac / MLV & incandescent dimmer switches.* UL Listed - dry, damp or wet location rated (see below). 100 - 277 VAC input. Integrated coated metal junction box case with 6 wiring knock-outs. Overload, over-current, and temperature protected. 10% minimum load required. Flicker free, 0-100% dimming range. Multi-output class 2 models listed below.

12 VDC Model #	24 VDC Model #	Wattage	Dimensions (L x W x H)	Weather Rating	Class 2	Case Color
SC-KVF-12030-TDWJ	SC-KVF-24030-TDWJ	30	6.5 x 3.5 x 1"	Damp	Y	Black
SC-KVF-12060-TDWJ	SC-KVF-24060-TDWJ	60	7.5 x 3.5 x 1"	Damp	Y	Black
SC-KVF-12060-TDWJN	N/A	60	7.5 x 3.5 x 1.6"	Wet	Y	Black
N/A	SC-KVF-24096-TDWJN	96	8.5 x 3.5 x 1.75"	Wet	Y	Black
SC-KVF-12100-TDWJN	N/A	100	8.5 x 3.5 x 1.75"	Wet	N	Black
SC-KVF-12150-TDWJN	SC-KVF-24150-TDWJN	150	10.25 x 4 x 1.75"	Wet	N	Black
SC-KVF-12200-TDWJN	SC-KVF-24200-TDWJN	200	10.25 x 4 x 1.75"	Wet	N	Black
SC-KVF-12300-TDWJN	SC-KVF-24300-TDWJN	300	11 x 4.25 x 1.75"	Wet	N	Black
Multi-Output Class 2 Models						
SC-KVF-C12180-TDWJ	N/A	180 (3x60)	11 x 4.25 x 1.75"	Wet	Y	Black
N/A	SC-KVF-C24192-TDWJ	192 (2x96)	11 x 4.25 x 1.75"	Wet	Y	Black
SC-KVF-C12300-TDWJ	N/A	300 (5x60)	12 x 4.25 x 1.75"	Wet	Y	Black
N/A	SC-KVF-C24288-TDWJ	288 (3x96)	13 x 4.25 x 1.75"	Wet	Y	Black



SC KVE Series - (replaces KVG series) Compact, hardwired and compatible with most ELV /Triac / MLV & incandescent dimmer switches,* plus 0-10V and 1-10V dimming. Adjustable output voltage (12-13 VDC, 24-26 VDC). Switchable dimming-PWM dimming with 10% minimum load OR voltage dimming with no minimum load. UL Listed - dry, damp or wet location rated (see below). 100 - 277 VAC input. Integrated coated aluminum junction box case with hinged cover, 8 wiring knock-outs & adjustable dividers between line and low voltage wiring compartments. Overload, over-current, and temperature protected. Flicker free, 0-100% dimming range.

12 VDC Model #	24 VDC Model #	Wattage	Dimensions (L x W x H)	Weather Rating	Class 2	Case Color
SC-KVE-12030-TMWJ1-BA	SC-KVE-24030-TMWJ1-BA	30	6.5 x 3.7 x 1.6"	Wet	Y	Black
SC-KVE-12060-TMWJ1-BA	SC-KVE-24060-TMWJ1-BA	60	7.4 x 3.7 x 1.7"	Wet	Y	Black
NA	SC-KVE-24096-TMWJ1-BA	96	7.4 x 3.8 x 1.7"	Wet	Y	Black
SC-KVE-12100-TMWJ1-BA	NA	100	7.4 x 3.8 x 1.7"	Wet	N	Black
SC-KVE-12150-TMWJ1-BA	SC-KVE-24150-TMWJ1-BA	150	8.1 x 4.6 x 1.7"	Wet	N	Black
SC-KVE-12200-TMWJ1-BA	SC-KVE-24200-TMWJ1-BA	200	8.1 x 4.6 x 1.7"	Wet	N	Black
SC-KVE-12300-TMWJ1-BA	SC-KVE-24300-TMWJ1-BA	300	9.5 x 4.9 x 1.7"	Wet	N	Black
SC-KVE-12500-TMWJ1-BA	SC-KVE-24600-TMWJ1-BA	500/600	11 x 5.5 x 2.0"	Wet	N	Black



MX Series - High performance & economical dimmable drivers. Hardwired and compatible with most Triac / MLV & incandescent dimmer switches.* ETL listed, IP20 indoor rated. 120 VAC input. Integrated coated metal junction box case with 6 wiring knock-outs. Overload, overcurrent, and temperature protected. 5% minimum load required.

12 VDC Model #	24 VDC Model #	Wattage	Dimensions (L x W x H)	Weather Rating	Class 2	Case Color
MX-ZV025012TK2AJ	MX-ZV025024TK2AJ	25	13.75 x 3 x 1"	Dry	Y	White
MX-ZV050012TK2AJ	MX-ZV050024TK2AJ	50	13.75 x 3 x 1"	Dry	Y	White
MX-ZV060012TK2AJ	MX-ZV060024TK2AJ	60	13.75 x 3 x 1.5"	Dry	Y	White
NA	MX-ZV096024TK6AJ	96	15 x 3 x 2.25"	Dry	Y	Black
MX-ZV100012TK6AJ	NA	100	15 x 3 x 2.25"	Dry	N	Black
MX-ZV150012TK6AJ	MX-ZV150024TK6AJ	150	16 x 3.375 x 2.3"	Dry	N	Black
MX-ZV200012TK6AJ	MX-ZV200024TK6AJ	200	16 x 3.375 x 2.3"	Dry	N	Black



In-Box Series - Mini drivers designed to mount cleanly inside a junction box. 120 VAC input.

12 VDC Model #	24 VDC Model #	Wattage	Dimensions (L x W x H)	Weather Rating	Class 2	Dimming
SCJ-ETF12060TD	SCJ-ETF24060TD	60	3.25 x 1.6 x 1"	Damp	Y	MLV/ELV/Triac
NA	SCJ-ETF24096TD	96	3.25 x 1.6 x 1"	Damp	Y	MLV/ELV/Triac



Northwest LED

* Please refer to our approved dimmer list for compatible dimmers.

Linear LED lighting

2428 Old Highway 99 S Rd. • Mount Vernon, WA • 360.422.5387 • www.NorthwestLED.com • info@northwestLED.com